


EQA SERIES | TANK CLEANING MACHINE

GEAR DRIVEN
FEMALE CONNECTION



Features :

- The powerful rotational solid stream jet effectively cleans the interior of tanks.
- No external power source is required; the rotation is driven solely by the flow of the cleaning liquid.
- Heat-resistant up to 85°C
- Its compact design allows for easy installation, even in small inlets.
- Easy insertion and removal, as the rotating nozzle is not locked into place.

Technical Data :

- Working pressure: 2 - 7 bar
- Recommended operating pressure: 5 bar
- Impact diameter: max. 4.5 mtr
- Reach diameter: max. 8 mtr
- Flow rate: 44 LPM to 68 LPM
- Spray angle: 360°
- Operating temperature: max. 85 °C
- Ambient temperature: max. 140 °C (30 min)
- Insertion opening: min. Ø 85 mm
- Materials: SS316, PTFE, PEEK
- Weight: approx. 0.62 kg
- No of Jet : 4 nos
- Driving Mechanism : Gear Driven



Note : We recommend to use 100 - 200 mesh strainer / filter

 E - 360°	PIPE CONN. SIZE	FLOW CAPACITY IN LPM AT DIFFERENT PRESSURE					NOZZLE ORIFICE DIAMETER (MM)	IMPACT DIAMETER (M)	REACH DIAMETER(M)
	1/2"	PRESSURE (BAR)							
		2.0	3.0	4.0	5.0	7.0			
EQA04.M2.XD	●	44.00	54.00	61.50	68.00	88.00	4	4.5	8

