


EQC SERIES | TANK CLEANING MACHINE

GEAR DRIVEN
FEMALE CONNECTION



Features :

- The powerful rotational solid stream jet effectively cleans the interior of tanks.
- No external power source is required; the rotation is driven solely by the flow of the cleaning liquid.
- Suitable for temp up to 95°C.
- Easy insertion and removal, as the rotating nozzle is not locked into place.

Technical Data :

- Working pressure: 2 - 7 bar
- Recommended operating pressure: 5 bar
- Impact diameter: max. 18 mtr
- Reach diameter: max. 24 mtr
- Flow rate: 200 LPM to 485LPM
- Spray angle: 360°
- Operating temperature: max. 95 °C
- Ambient temperature: max. 140 °C (30 min)
- Insertion opening: min. Ø 230mm
- Materials: SS316, PTFE, PEEK
- Weight: approx. 7.5 kg
- No of Jet : 4 nos
- Driving Mechanism : Gear Driven



Note : We recommend to use 80 - 100 mesh strainer / filter

 E - 360°	PIPE CONN. SIZE	FLOW CAPACITY IN LPM AT DIFFERENT PRESSURE					NOZZLE ORIFICE DIAMETER (MM)	IMPACT DIAMETER (M)	REACH DIAMETER (M)
	1 1/2"	PRESSURE (BAR)							
		2.0	3.0	4.0	5.0	7.0			
EQC08.M2.XH	●	200.00	244.00	282.00	315.00	373.00	8	15	20
EQC10.M2.XH	●	259.00	317.00	366.00	410.00	485.00	10	18	24

